

ALMANDO MASTERPLAY - INSTALLATION MANUAL (ENGLISH)

IMPORTANT You can connect **almando Masterplay** to only **ONE** Bang & Olufsen Link product! If you have multiple B&O link products, you have to resolve the common Masterlink wiring. Each B&O link product has to be operated with its own **almando Masterplay**.

**The almando Masterplay is compatible with these B&O link products:
BeoLab 3500, BeoLab 2000, LCS 9000, BeoLink Passive, BeoLink Active**

SETUP These steps must be done only once to getting started:

1. Connect the B&O link product to the mains power supply.
2. Press the TIMER key on the Masterlink speaker or on the BeoLink IR eye. The TIMER LED lights up red.
3. Connect **the almando Masterplay** and the B&O link product with a Masterlink cable.
4. Connect the **almando Masterplay** to the mains power supply.
5. **IMPORTANT: Wait 20 seconds! (During this time, the registration is done)**
6. Connect the audio source to the **almando Masterplay** (e.g. B&O Playmaker, B&O BeoSound 5, Sonos Connect, Apple Airport Express).
7. Start the playback on the connected source.
8. **Now configure DIP-switch 2:**
 - DIP 2 ON (top) for sources with trigger voltage (Powerlink), e.g. Playmaker, BeoVision
 - DIP 2 OFF (bottom) for sources without trigger voltage, e.g. Sonos Connect, Apple Airport Express (operating mode: automatic signal detection)
- (9.) If necessary configure DIP-switch 1 for the turn-off-delay: (only for operating mode automatic signal detection):
 - DIP 1 ON (top) turn-off-delay ½ minute
 - DIP 1 OFF (bottom) turn-off-delay 2 minutes
10. Configure your B&O link product to **option 6** in order to adjust the sound settings to your personal preference (**in particular, the maximum volume** for a pleasant volume control with your iPhone for example). This can be stored permanently as the default setting.
For Beolab 3500 / LCS 9000 we recommend: vol.60
To do this, you need a B&O remote control (e.g. Beo4 or Beolink 1000). The required key sequence will vary depending on the B&O remote control or type of B&O link product. Detailed information is available in your B&O manual.
11. **IMPORTANT:** Finally, configure your B&O link product to **option 0**.

NOTE For the daily operation of your Bang & Olufsen link product you don't need the B&O remote control anymore. Just start the playback on the connected source and the B&O link product will be switched on automatically. The volume can be controlled on the source itself (e.g. with the iPhone)